

Refine Search

Search Results -

Terms	Documents
L15	3

Database:

US Pre-Grant Publication Full-Text Database
US Patents Full-Text Database
US OCR Full-Text Database
EPO Abstracts Database
JPO Abstracts Database
Derwent World Patents Index
IBM Technical Disclosure Bulletins

Search:

L16

Refine Search

Recall Text

Clear

Interrupt

Search History

DATE: Monday, March 21, 2005 [Printable Copy](#) [Create Case](#)

Set Name Query

side by side

Hit Count Set Name

result set

DB=PGPB; THES=ASSIGNEE; PLUR=YES; OP=OR

L16 L15

3 L16

L15 L14 and can

3 L15

L14 "10/083,784"

3 L14

DB=USPT; THES=ASSIGNEE; PLUR=YES; OP=OR

L13 L1 and (vehicle same condition\$)

2 L13

L12 L1 and (steer\$ and brak\$)

1 L12

L11 L1 and paging

3 L11

L10 L1 and (chip adj set\$)

0 L10

L9 L1 and chipset\$

0 L9

L8 L1 and (satellit\$ or gps)

3 L8

L7 L1 and ((satellit\$ or gps) and chipset\$)

0 L7

L6 L1 and roam\$

1 L6

L5 L1 and mother\$

0 L5

L4 L1 and motherboard

0 L4

<u>L3</u>	L1 and gateway	2	<u>L3</u>
<u>L2</u>	L1 and obd	1	<u>L2</u>
<u>L1</u>	6611740.pn. or 6246325.pn. or 6151491.pn. or 6429812.pn.	4	<u>L1</u>

END OF SEARCH HISTORY

[First Hit](#) [Fwd Refs](#)

[Previous Doc](#)

[Next Doc](#)

[Go to Doc#](#)

End of Result Set



Generate Collection

Print

L6: Entry 1 of 1

File: USPT

Nov 21, 2000

DOCUMENT-IDENTIFIER: US 6151491 A

TITLE: Mobile voice message/electronic mail system

Detailed Description Text (16):

Registration may be enabled or disabled individually for each class of mobile phone, e.g., home or roam (explained below), by means of control bits in the system parameter overhead message. The system parameter overhead message also contains the identification number of the serving cellular system from which the mobile phone determines whether it is a "home" or a "roam" mobile phone. Each mobile phone contains, in its internal memory, an entry indicating the identity of its home cellular system and an entry indicating the cellular systems (which may be the home cellular system) in which it has most recently registered successfully. It also stores a value for the cellular system used to determine when it is scheduled to re-register in that cellular system.

Detailed Description Text (26):

Registration may be enabled or disabled individually for each class of mobile phone, e.g., home or roam (explained below), by means of control bits in the system parameter overhead message in step R24. The system parameter overhead message also contains the identification number of the serving cellular system from which the mobile phone determines whether it is a "home" or a "roam" mobile phone in step R26. Each mobile phone contains, in its internal memory, an entry indicating the identity of its home cellular system and an entry indicating the cellular systems (which may be the home cellular system) in which it has most recently registered successfully. It also stores a value for the cellular system used to determine when it is scheduled to re-register in that cellular system.

[Previous Doc](#)

[Next Doc](#)

[Go to Doc#](#)

End of Result Set

Generate Collection

Print

L2: Entry 1 of 1

File: USPT

Aug 26, 2003

DOCUMENT-IDENTIFIER: US 6611740 B2

TITLE: Internet-based vehicle-diagnostic system

Brief Summary Text (4):

The Environmental Protection Agency (EPA) requires vehicle manufacturers to install on-board diagnostics (OBD-II) for monitoring light-duty automobiles and trucks beginning with model year 1996. OBD-II systems (e.g., microcontrollers and sensors) monitor the vehicle's electrical and mechanical systems and generate data that are processed by a vehicle's engine control unit (ECU) to detect any malfunction or deterioration in the vehicle's performance. Most ECUs transmit status and diagnostic information over a shared, standardized electronic buss in the vehicle. The buss effectively functions as an on-board computer network with many processors, each of which transmits and receives data. The primary computers in this network are the vehicle's electronic-control module (ECM) and power-control module (PCM). The ECM typically monitors engine functions (e.g., the cruise-control module, spark controller, exhaust/gas recirculator), while the PCM monitors the vehicle's power train (e.g., its engine, transmission, and braking systems). Data available from the ECM and PCM include vehicle speed, fuel level, engine temperature, and intake manifold pressure. In addition, in response to input data, the ECU also generates 5-digit 'diagnostic trouble codes' (DTCs) that indicate a specific problem with the vehicle. The presence of a DTC in the memory of a vehicle's ECU typically results in illumination of the 'Service Engine Soon' light present on the dashboard of most vehicles.

Brief Summary Text (5):

Data from the above-mentioned systems are made available through a standardized, serial 16-cavity connector referred to herein as an 'OBD-II connector'. The OBD-II connector typically lies underneath the vehicle's dashboard. When a vehicle is serviced, data from the vehicle's ECM and/or PCM is typically queried using an external engine-diagnostic tool (commonly called a 'scan tool') that plugs into the OBD-II connector. The vehicle's engine is turned on and data are transferred from the engine computer, through the OBD-II connector, and to the scan tool. The data are then displayed and analyzed to service the vehicle. Scan tools are typically only used to diagnose stationary vehicles or vehicles running on a dynamometer.

Brief Summary Text (6):

Some vehicle manufacturers also include complex electronic systems in their vehicles to access and analyze some of the above-described data. For example, General Motors includes a system called 'On-Star' in some of their high-end vehicles. On-Star collects and transmits data relating to these DTCs through a wireless network. On-Star systems are not connected through the OBD-II connector, but instead are wired directly to the vehicle's electronic system. This wiring process typically takes place when the vehicle is manufactured.

Brief Summary Text (8):

Embodiments of the invention can provide a wireless, internet-based system for monitoring a vehicle. For example, embodiments of the invention can access data from a vehicle, analyze it, and make it available to organizations (e.g. an

automotive dealership or service center) over the internet so that the vehicle's performance can be analyzed accurately and in real-time. Data are accessed through the same OBD-II connector used by conventional scan tools. In this way, the invention collects data similar to those collected by scan tools, only they are collected in real-time while the vehicle is actually being driven. The invention also provides an Internet-based web site to view these data. The web site also includes functionality to modify the type of data being collected, e.g. the type of diagnostic data or the frequency at which it is collected. The data can be collected and viewed over the Internet without having to bring the vehicle in for service. The data include, for example, DTCs and mechanical and electrical data stored in the vehicle's engine computer.

Brief Summary Text (28):

The wireless appliance used to access and transmit the vehicle's data is small, low-cost, and can be easily installed in nearly every vehicle with an OBD-II connector in a matter of minutes. It can also be easily transferred from one vehicle to another, or easily replaced if it malfunctions.

Detailed Description Text (3):

The wireless appliance 13 disposed within the vehicle 12 collects diagnostic data from the vehicle's engine computer 15. The engine computer 15 retrieves data stored in its memory and sends it along a cable 16 to the wireless appliance 13. The appliance 13 typically connects to the OBD-II connector located under the dash in all vehicles manufactured after 1996. It includes a data-collection component (not shown in the figure) that formats the data in a packet and then passes the packet to a data-transmission component, which sends it through a cable 17 to an antenna 14. To generate the data, the wireless appliance 13 queries the vehicle's computer 15 at a first time interval (e.g. every 20 seconds), and transmits a data set at a longer time interval (e.g. every 10 minutes). These time intervals are specified in a data-collection 'schema', described in more detail below.

Detailed Description Text (16):

The parameters listed in Table 1 were measured from a Ford Crown Victoria. Similar sets of data are available for nearly all vehicles manufactured after 1996 that have an OBD-II connector. In addition to these, hundreds of other vehicle-specific parameters are also available from the vehicle's computer.

[Previous Doc](#)

[Next Doc](#)

[Go to Doc#](#)

[First Hit](#) [Fwd Refs](#)

[Previous Doc](#)

[Next Doc](#)

[Go to Doc#](#)



Generate Collection

Print

L3: Entry 1 of 2

File: USPT

Aug 26, 2003

DOCUMENT-IDENTIFIER: US 6611740 B2

TITLE: Internet-based vehicle-diagnostic system

Brief Summary Text (18):

The host computer system typically features at least one web-hosting computer that hosts the web site, and at least one, separate gateway computer that receives the outgoing data packet and sends the incoming data packet. In this embodiment the web site features a first web page that displays at least a single vehicle diagnostic datum. For example, the first web page can include data fields describing: i) a name of the diagnostic datum; ii) units corresponding to the diagnostic datum; and iii) a numerical value corresponding to the diagnostic datum. Multiple sets of diagnostic data, each received by the host computer system at a unique time and date, can also be displayed on the web page. The page can also include a graphical representation of the sets of diagnostic data, e.g. a time-dependent plot of the data.

Brief Summary Text (22):

The gateway computer that receives the outgoing data packet and sends the incoming data packet is connected to the network, typically through an Internet-based connection or a digital communication line.

CLAIMS:

8. The system of claim 1, wherein the system comprises a host computer system that includes at least one web-hosting computer that hosts an internet-based web site, and at least one, separate gateway computer that receives outgoing data and sends incoming data.

19. The system of claim 8, wherein the gateway computer that receives the outgoing data packet and sends the incoming data packet is connected to the network.

20. The system of claim 19, wherein the gateway computer is connected to a digital communication line that is connected to the network.

[Previous Doc](#)

[Next Doc](#)

[Go to Doc#](#)



L11: Entry 2 of 3

File: USPT

Jun 12, 2001

DOCUMENT-IDENTIFIER: US 6246325 B1

TITLE: Distributed communications system for reducing equipment down-time

Abstract Text (1):

A system and method to more efficiently exchange information between a service provider, such as a semiconductor company, and its remote equipment units. The system capable of immediately handling a number of information items, each belonging to a different remote equipment unit is disclosed. The system includes a central controller configured for interfacing with a plurality of remote equipment units via a wireless network. The central controller is configured to receive information from each remote equipment unit via a wireless network. This information includes alarm conditions and corresponding requests for repair. Each of the remote equipment units is identified by a unique code which is included in the information transmitted to the computer to identity the source (i.e., identity of the transmitting remote equipment unit). The central controller uses the code of the transmitting remote equipment unit to retrieve the corresponding data record stored in its memory. The repair person identified in the selected data record is then contacted automatically, e.g., by wireless paging. The system may be programmed with a pre-determined routine maintenance schedule for each remote equipment unit. Based on this schedule, the system automatically contacts the appropriate repair person by wireless paging and dispatches the repair person to the corresponding remote equipment unit for routine maintenance. Thus, the down-time of the remote equipment unit is reduced because the alarm condition is immediately transmitted to the central controller and the corresponding repair person is contacted automatically. There is no undesired down-time before monitoring personnel notices the alarm condition and contacts the corresponding repair person.

Brief Summary Text (13):

In accordance with one embodiment of the present invention, a distributed communications system capable of immediately handling a number of information items, each belonging to a different remote equipment unit is disclosed. The distributed communications system includes a central controller configured for interfacing with a plurality of remote equipment units via a wireless network. The central controller is configured to receive information from each remote equipment unit via a wireless network. This information includes alarm conditions and corresponding requests for repair. Each of the remote equipment units is identified by a unique code which is included in the information transmitted to the computer to identity the source (i.e., identity of the transmitting remote equipment unit). The central controller uses the code of the transmitting remote equipment unit to retrieve the corresponding data record stored in its memory. The repair person identified in the selected data record is then contacted automatically, e.g., by wireless paging.

Brief Summary Text (15):

The distributed communications system of the present invention is also capable of keeping track of routine maintenance schedules. The distributed communications system may be programmed with a pre-determined routine maintenance schedule for each remote equipment unit. Based on this schedule, the distributed communications system automatically contacts the appropriate repair person by wireless paging and

dispatches the repair person to the corresponding remote equipment unit for routine maintenance.

Detailed Description Text (13):

Base-station 208 is also configured to transmit signals to the wireless pagers of the repair person via paging channel 240. Generally, base-station 208 receives paging signals generated by central controller 130 and forwards these paging signals to a paging tower 250 via paging channel 240. Paging tower 250 is configured to transmit these paging signals to the wireless pagers of the repair persons. In the preferred embodiment, base-station 208 and MTSO 210 are part of a code-division multiple-access (CDMA) spread spectrum communication system. Additionally, wireless network 120 may be designed in accordance with the Telecommunications Industry Association Electronic Industries Association (TIA/EIA) Interim Standard 95 (IS-95) standard, entitled "Mobile Station Base-Station Compatibility Standard for Dual-Mode Wideband Spread Spectrum Cellular System." Alternatively, the wireless communication system may be designed in accordance with the ANSI J-STD-008, standard entitled "Personal Station-Base-Station Compatibility Requirements for 1.8 to 2.0 GHz Code Division Multiple Access (CDMA) Personal Communications Systems."

CLAIMS:

7. The method of claim 1, wherein the service request comprises a paging message to a pager of the repair person.
14. The central controller of claim 8, wherein the service request comprises a paging message to a pager of the repair person.

[Previous Doc](#)

[Next Doc](#)

[Go to Doc#](#)

[First Hit](#) [Fwd Refs](#)

[Previous Doc](#)

[Next Doc](#)

[Go to Doc#](#)



Generate Collection

Print

L13: Entry 1 of 2

File: USPT

Aug 26, 2003

DOCUMENT-IDENTIFIER: US 6611740 B2

TITLE: Internet-based vehicle-diagnostic system

Brief Summary Text (30):

Moreover, software schemas that update the type or frequency of the vehicle's data can be directly downloaded to specific wireless appliances or groups of wireless appliances (corresponding, e.g., to a fleet of vehicles or a group of vehicles having the same year, make, or model). This makes it possible to collect data that specifically elucidates a problem with the vehicle that may occur only under certain driving conditions.

[Previous Doc](#)

[Next Doc](#)

[Go to Doc#](#)

End of Result Set

Generate Collection

Print

L12: Entry 1 of 1

File: USPT

Aug 6, 2002

DOCUMENT-IDENTIFIER: US 6429812 B1

TITLE: Mobile communication device

Brief Summary Text (35):

Systems which integrate GPS, GLONASS, LORAN or other positioning systems into vehicular guidance systems are well known, and indeed navigational purposes were prime motivators for the creation of these systems. Radar, laser, acoustic and visual sensors have all been applied to vehicular guidance and control, as well. For example, U.S. Pat. No. 4,757,450 relates to a reflected beam system for detecting a preceding vehicle, in order to allow control over intervehicular spacing. U.S. Pat. No. 4,833,469 relates to an obstacle proximity sensor, employing, e.g., a radar beam to determine distance and relative velocity of an obstacle. U.S. Pat. No. 5,600,561 relates to a vehicle distance data processor which computes a velocity vector based on serial timepoints. U.S. Pat. No. 4,552,456 relates to an optical pulse radar for an automobile. U.S. Pat. No. 4,543,577 relates to a moving obstacle detection system for a vehicle, using Doppler radar. U.S. Pat. No. 4,349,823 relates to an automotive radar system for monitoring objects in front of the vehicle. U.S. Pat. No. 5,473,538 relates to a collision judging system for a vehicle, triggered by a braking event and determining a distance to an obstacle in front of the vehicle. U.S. Pat. No. 4,168,499 relates to an anti-collision radar system. U.S. Pat. No. 4,626,850 relates to a vehicle detection and collision avoidance apparatus, using an acoustic sensor. U.S. Pat. No. 4,028,662 relates to a passing vehicle signaling apparatus, to detect adjacent vehicles during a lane change. U.S. Pat. No. 5,541,590 relates to a vehicle crash predictive and evasive system, employing neural networks. U.S. Pat. No. 5,646,612 relates to a vehicle collision avoidance system, using an infrared imaging system. U.S. Pat. No. 5,285,523 relates to a neural network system for recognizing driving conditions and controlling the vehicle in dependence thereon. U.S. Pat. No. 5,189,619 relates to an artificial intelligence based adaptive vehicle control system. U.S. Pat. No. 5,162,997 relates to a driver-adaptive automobile control system. U.S. Pat. No. 3,689,882 relates to an anti-collision radar system for detecting obstacles or on-coming vehicles.

Brief Summary Text (47):

The following references, incorporated herein by reference, relate to GPS, position sensors, sensor data analysis, and associated technologies: "Fuzzy Logic Simplifies Complex Control Problems", Tom Williams, Computer Design, Mar. 1, 1991. "Methods for Performance Evaluation of Coordinate Measuring Machines, ANSI/ASME B89.1.12M-1985," An American National Standard, published by The American Society of Mechanical Engineers, USA, 1985. "Neural Network And Fuzzy Systems--A Dynamical Systems Approach To Machine Intelligence", Bart Kosko, Prentice Hall 1992; Englewood Cliffs, N.J.; pp. 13, 18, 19. "New Airbuses to Use Laser Inertial Reference Systems for Navigation," Litton Systems, Aircraft Engineering, pp. 10-11, June 1983. "Reasoning For Interpreting Sensor Data," P. J. Braspenning, International Conference Intelligent Autonomous Vehicles, Amsterdam, 1986. "Sensor Failure Detection Using a Hybrid Analytical/Intelligent Algorithm," George Vachstevanos, International Conference Intelligent Autonomous Vehicles, Amsterdam, 1986. "An/PRC-112 Multi-Mission Transceiver", published by Motorola, Inc.,

Communications Division, Copyright 1991. "Combat Rescue. One Pass is All You Get. With PLS, One Pass is All You Need. PLS (Personnel Locator System)", published jointly by Cubic Defense Systems and Motorola, Inc., publication date unknown. "Artificial intelligence in the control and operation of construction plant-the autonomous robot excavator" published 1993. "Automation and Robotics in Construction"-vol. 1 by FHG (9 pgs.) believed to have been published on or about June 1991. "Backhoe Monitor" by IHC-3 Pgs.-Publication date unknown but believed to be prior to one year before the filing date. Ashjaee, J., et al., "Precise Positioning Using a 4-Channel C/A Code GPS Receiver," IEEE pp. 236-244, 1984. Auch, W., et al., "Fibre Optic Gyroscope," 1984. B. Krogh et al., "Integrated Path Planning and Dynamic Steering Control for Autonomous Vehicles," 1986. Brockstein, A., "GPS-Kalman-Augmented Inertial Navigation System Performance," Naecom '76 Record, pp. 864-868, 1976. Brodie, K., et al., Performance Analysis of Integrated Navigation Systems, computer applications software technology, no date. Brooks, R., "Solving the Fine-Path Problem by Good Representation of Free Space," IEEE Transactions on Systems, Man, and Cybernetics, pp. 190-197, March-April, 1983. Brown, R., "Kalman Filtering Study Guide--A Guided Tour," Iowa State University, pp. 1-19, 1984. Brown, R., Random Signal Analysis & Kalman Filtering, Chapter 5, pp. 181-209, no date. Bundorf, R. "The Influence of Vehicle Design Parameters on Characteristic Speed and Understeer," January 1967. C. McGillem et al., "Infra-Red Location System for Navigation of Autonomous Vehicles," IEEE, pp. 1236-1238, 1988. Canny, J., "A Computational Approach to Edge Detection," pp. 184-203, 1985. Culshaw, B., et al., "Fibre Optic Gyroscopes In Inertial Navigation," no date. D. Daniellet al., "Kinematics and Open-loop Control of an Inertial-Based Mobile Platform," pp. 346-351 1985. D. Feng, "Satisficing Feedback Strategies for Local Navigation of Autonomous Mobile Robots," May 5, 1989. D. Kriegman et al., "Generic Models for Robot Navigation," pp. 746-751, 1988. D. Kuan et al., "Model-based Geometric Reasoning for Autonomous Road Following," pp. 416-423, 1987. D. Kuan, "Autonomous Robotic Vehicle Road Following," IEEE Transactions on Pattern Analysis and Machine Intelligence, pp. 647-658, 1988. D. Rogers et al., Mathematical Elements for Computer Graphics, pp. 144-155, Dec. 8, 1989. D. Touretzky et al., "What's Hidden in the Hidden Layers?," Byte, pp. 227-233, August 1989. Data Fusion in Pathfinder and Travtek, Roy Sumner, VNIS '91 conference, October 20-23, Dearborn, Mich. Database Accuracy Effects on Vehicle Positioning as Measured by the Certainty Factor, R. Borcherts, C. Collier, E. Koch, R. Bennet, VNIS '91 conference from October 20-23, Dearborn, Mich. Daum, F., et al., "Decoupled Kalman Filters for Phased Array Radar Tracking," IEEE Transactions on Automatic Control, pp. 269-283, March 1983. Denavit, J. et al., "A Kinematic Notation for Lower-Pair Mechanisms Bases on Matrices," pp. 215-221, June, 1955. Dickmanns, E. et al., "Guiding Land Vehicles Along Roadways by Computer Vision", The Tools for Tomorrow, Oct. 23, 1985. Dickmanns, E., "Vehicle Guidance by Computer Vision," no date. Divakaruni, S., et al., "Fast Reaction and High Reliability of Strapdown Navigation Systems Using Ring Laser Gyros," IEEE pp. 315-322, 1984. E. Dickmanns et al., "A Curvature-based Scheme for Improving Road Vehicle Guidance by Computer Vision," SPIE's Cambridge Symposium on Optical and Optoelectronic Engineering, October 1986. E. Udd, "Fiberoptic v. Ring Laser Gyros: An Assessment of the Technology," Laser Focus/Electro-Optics, pp. 64-74, December 1985. Edward J. Krakiwsky, "A Kalman Filter for Integrating Dead Reckoning, Map Matching and GPS Positioning", IEEE Plans '88 Position Location and Navigation Symposium Record, Kisseemee, Fla. USA, Nov. 29-Dec. 2, 1988, pp. 39-46. Euler, W., et al., "A Perspective on Civil Use of GPS, The Institute of Navigation; 36th Annual Meeting, pp. 1-7, 1980. Fusion of Multisensor Data, John M. Richardson, Kenneth A. Marsh; International Journal of Robotics Research; vol. 7, no. 6; December 1988; pp. 78-87. Fuzzy Systems and Applications, United Signals and Systems, Inc., Bart Kosko with Fred Watkins, Jun. 5-7, 1991. G. Geier, et al., "Design of an Integrated Navigation System for Robotic Vehicle Application," Journal of the Institute of Navigation. G. Wilfong, "Motion Planning for an Autonomous Vehicle," AT&T Bell Laboratories, pp. 529-533, 1988. GPS Technology and Opportunities, Clyde Harris and Roy Sikorski Expo Comm China '92, Beijing, China, Oct. 30-Nov. 4, 1992. GPS World, News and Applications of the Global Positioning System, March/April 1990. GPS-90 Tutorials, The Institute of

Navigation, Sep. 17-18, 1990, pp. 1-28. Greenspan, R., et al. "Accuracy of Relative Positioning by Interferometry with Reconstructed Carrier CPS: Experimental Results," Third International Symposium on Satellite Doppler Positioning, pp. 1-19, February 1982. H. Hatwal et al., "Sonic Inverse Solutions to an Automobile Path-tracking Problem with Input Control of Steering and Brakes," Vehicle System Dynamics, pp. 61-71, 1986. H. Nasr et al., "Landmark Recognition for Autonomous Mobile Robots," pp 1218-1223, 1988. H. Nii, "Blackboard Application Systems, Blackboard Systems from a Knowledge Engineering Perspective," The AI Magazine, pp. 82-89, August 1986. H. Nii, "Blackboard Systems: The Blackboard Model Problem-solving and the Evolution of Blackboard Architectures," The AI Magazine, pp. 38-53, Summer 1986. H. Wunsche, "Detection and Control of Mobile Robot Motion by Real-Time Computer Vision," Mobile Robots, pp. 100-104, 1986. H. Yamazaki et al., "Autonomous Land Vehicle Using Millimeter Wave Sensing Systems," Proceedings of the 5th International Symposium on Robotics in Construction, June 1988. Hiroshige et al., "Error Analysis of Electronic Roll Stabilization for Electronically Scanned Antennas", IEEE 1991 pp. 71-75. I. Cox, "Blanche: An Autonomous Robot Vehicle for Structured Environments," AT&T Bell Laboratories, pp. 978-982, 1988. IEEE Communications Magazine, vol. 26, No. 7, July 1988 (New York) P. Enge et al. "Differential operation of global positioning system" pp. 48-59. IEEE Journal of Robotics & Automation, vol. 4, No. 3, June 1988, IEEE (New York), C. Isik et al. "Pilot Level of a Hierarchical Controller for an Unmanned Mobile Robot", pp. 241-255. IEEE Journal of Robotics & Automation, vol. 4, No. 4, August 1988, IEEE (New York) J. LeM "Domain-dependent reasoning for visual navigation of roadways, pp. 419-427 (Nissan) Mar. 24, 1988. IEEE Plans '86 Position Location and Navigation Symposium, November 1986, S. Bose: "GPS/PLRS aided inertial land navigation system performance", pp. 496-504. IEEE Plans '86 Position Location and Navigation Symposium, November 1986, S. Bose: "GPS/PLRS aided inertial land navigation system performance", pp. 496-504. IEEE Plans '90 Position Location and Navigation Symposium, Las Vegas, Mar. 20-23, 1990, IEEE New York, N.Y., US. Hunter et al: Vehicle navigation using differential GPS, pp. 392-398. IEEE Proceedings, vol. 77, No. 11, Nov. 11, 1989, L. Schuchman et al.: "Applicability of an augmented GPS for navigation in the National Airspace system", pp. 1709-1727, 1713, 1717, FIGS. 1-8. IEEE Transactions on Pattern Analysis, vol. 10, No. 5 September 1988. IEEE (New York), D. Kuan et al., "Autonomous robotic vehicle road following" pp. 648-658. Iijima, J., et al., "A Locomotion Control System for Mobile Robots," no date. Integration of GPS and Dead Reckoning Navigation Systems, Wei-Wen Kao, VNIS '91 conference from October 20-23, Dearborn, Mich. J. Borenstein et al., "The Vector Field Histogram-Fast Obstacle Avoidance for Mobile Robots," IEEE Journal of Robotics and Automation, July 1989. J. Collins, "GPS Equipment Survey, GPS-What does it all mean?," P.O.B., June-July 1987 pp. 12-22. J. Crowley, "Asynchronous Control of Orientation and Displacement in a Robot Vehicle," pp. 1277-1288, 1989. J. Crowley, "Part 3: Knowledge Based Supervision of Robotics Systems," 1989 IEEE Conference on Robotics and Automation, pp. 37-42, 1989. J. Dixon, "Linear and Non-linear Steady State Vehicle Handling," Proceedings of the Institute of Mechanical Engineers, pp. 173-186, 1988. J. Nielson, et al. "GPS Aided Inertial Navigation," IEEE AES Magazine, pp. 20-26, March 1986. J. Oliver et al., "A Navigation Algorithm for an Intelligent Vehicle with a Laser Rangefinder," pp. 1145-1150, 1986. J. Sennott et al., "Study of Differential Processing and Kalman Filtering of Bay Saint Louis Test Data, Ch 1-5, 1987. Jacob, T., Integrated Navigation System for Approach Guidance for Regional Air-Traffic Using GPS, no date. Johnson, C. "In-Flight Transfer Alignment/Calibration of a Strapdown INS that Employs Carouseled Instruments and IMV Indexing," no date. Jorgensen, "18-Satellite Constellations," pp. 9-12, 1980. Kaczmarek, K. W., "Cellular Networking: A Carrier's Perspective", 39th IEEE Vehicular Technology Conference, May 1, 1989, vol. 1, pp. 1-6. Kanayama, Y., et al., "A Vehicle Control Architecture-Smooth Driver," Stanford University, no date. Kanayama, Y., et al., "Trajectory Generation for Mobile Robots," no date. Kao, M., et al., "Multiconfiguration Kalman Filter Design for High-Performance GPS Navigation," IEEE Transactions on Automatic Control, pp. 304-314, March 1983. Khatib, O., "Real-time Obstacle Avoidance for Manipulators and Mobile Robots", pp. 500-505, 1985. Knowledge Representation in Fuzzy Logic, Lotfi A. Zadeh, IEEE

Transactions on Knowledge and Data Engineering, vol. 1, No. 1, March 1989. Kowalski et al., "Music Algorithm Implementation for Shipboard HF Radio Direction Finding", IEEE, 1991, pp. 0943-0947. Kuritsky, M., et al., "Inertial Navigation," Proceedings of the IEEE, pp.1156-1176, October 1983. L. Matthies et al., "Integration of Sonar and Stereo Range Data Using a Grid-based Representation," Computer Science Department and Robotics Institute, Carnegie-Mellon University, pp. 727-733, 1988. Lerner, E., "Gyros in Business Aircraft," Aerospace America, pp. 66-69, October 1984. Lozano-Perez, T., et al., "An Algorithm for Planning Collision-free Paths among Polyhedral Obstacles," Communications of the ACN, pp. 560-570, October 1979. Luh, J., et al., "Resolved-acceleration Control of Mechanical Manipulators," IEEE Transactions on Automatic Control, pp. 468-475, June 1980. M. Dailey et al., "Autonomous Cross-Country Navigation with the ALV," Hughes Artificial Intelligence Center, pp. 718-726, 1988. M. Grewal et al., "Application of Kalman Filtering to the Calibration and Alignment of Inertial Navigation Systems," IEEE, pp. 65-72, 1986. MacAdam, C., "Application of an Optimal Preview Control for Simulation of Closed-Loop Automobile Driving," IEEE Transactions on Systems, Man, and Cybernetics, pp. 393--399, June 1981. Martin, E., "Aiding GPS Navigation Functions," Naecom '76 Record, pp. 849-856, 1976. Mueller, C., et al., "Laser Gyro Land Navigation System Performance Predictions and Field Results," IEEE, 1984. Navigation "Surveys" Summer, 1984, vol. 31, #2, by P. F. MacDoran et al. Navigation Journal of The Institute of Navigation, vol. 32. No. 4, Winter, 1985-86, Printed in U.S.A., "Terrestrial Evaluation of the GPS Standard Positioning Service": by Francis W. Mooney. Navigation Journal of the Institute of Navigation, vol. 33, No. 4, Winter, 1986-87, Printed in U.S.A., "DiffStar: A Concept for Differential GPS in Northern Norway", by Hermod Fjereide. Navigation Journal of the Institute of Navigation, vol. 36, No. 3, Fall, 1989, Printed in U.S.A., "Loran-C Vehicle Tracking in Detroit's Public Safety Dispatch System", by Laurence J. Cortland. Navstar GPS Space Segment/Navigation User Interface, Rockwell International Corporation, Nov. 30, 1987. Nedley, A., et al., "A New Laboratory Facility for Measuring Vehicle Parameters Affecting Understeer and Brakesteer," pp. 1-20, Jun. 2, 1972. Nitao, J., et al., "A Pilot for a Robotic Vehicle System," pp. 951-955, no date. Orin, D., "Supervisory Control of a Multi-legged Robot," The International Journal of Robotics Research, pp. 79-91, Spring 1982. P. Muir, et al. "Kinematic Modeling for Feedback Control of an Omnidirectional Wheeled Mobile Robot," pp. 1772-1778, 1987. Parkinson, B., et al., "NAVSTAR: Global Positioning System--Ten Years Later," Proceedings of the IEEE, pp. 1178-1186, 1983. Patent Abstract of Japan, vol. 12, No. 290 (p. 742) Aug. 8, 1988 & JPA 63066479 (Nissan) Mar. 24, 1988. Patent Abstract of Japan, vol. 13, No. 306 (p. 897) Jul. 13, 1989 & JPA 1079679 (Toyota) Mar. 24, 1989. Patent Abstract of Japan, vol. 13, No. 306 (p. 897) Jul. 7, 1989 & JPA 1079679 (Toyota) Mar. 24, 1989. Proceeding PR '88, The Computer Society Conference on Computer Vision & Pattern Recognition, Jun. 5-9, 1988 (Ann Arbor) S. Dickinson et al., "An expert vision system for Autonomous Land Vehicle Road Following", pp. 826-831. Proceedings 1987 IEEE Conference Mar. 31, 1987 Apr. 3, 1987, vol. 2, L. Conway et al.: "Teleautonomous systems: Methods & Architectures for Intermingling autonomous & Telerobotic Technology" pp. 1121 1130. Proceedings 1987 IEEE International Conference on Robotics & Automation. Mar. 31-Apr. 3, 1987. (Raleigh, N.C.), sponsored by IEEE Council on Robotics & Automation, vol. 3, D. McMenthon, "A zero-bank algorithm for Inverse Perspective of a Road from Single Image, pp. 1444-1449. Proceedings of 1988 IEEE International Conference on Robotics & Automation, vol. 2, Apr. 24-29, 1988, Philadelphia, IEEE Computer Soc. Press (Washington D.C.), L. E. Banta: "A self turning navigation algorithm", pp. 1313-1314. Proceedings of the IEEE-F Communications, Radar and Signal Processing, vol.

Brief Summary Text (48):

127, No. Apr. 2, 1980, Stevenage, GB. Blair et al: receivers for the NAVSTAR global positioning system, pp. 163-167. Product Announcement, "Measurement Methods-Coordinate Measuring Specialists," published by Measurement Methods, Baltimore, Md., USA, publication date unknown. Product Brochure entitled "KOBA-Step Precision Step Gauge," published by Kolb & Baumann GmbH & Co., Germany, 1992. Product Brochure, "Mobile Calibration Station Utilizing Surveillance Masters," published by

Glastonbury Gage, USA, publication date unknown. R. Cox et al., "Design for Maintainability: Litton's New Family of RLG Inertial Navigation Systems," IEEE, pp. 115-119, 1986. R. Dork, "Satellite Navigation Systems for Land Vehicles," IEEE AES Magazine, pp. 2-5, May 1987. R. Dunlay, "Obstacle Avoidance Perception Processing for the Autonomous Land Vehicle," pp. 912-917, 1988. R. Majure et al., "Comparison of Laser Gyro IMU Configurations for Reentry Systems," IEEE, pp. 96-100, 1986. Randolph Hartman, "Integrated Laser Inertial/GPS Navigation (GPIRS)," Publication of Honeywell Inc., February, 1990, from a presentation of the Royal Institute of Navigation NAV '89" Satellite Navigation Conference, October, 1989. Raol, J., et al., "On the Orbit Determination Problem," IEEE Transactions on Aerospace and Electronic Systems, pp. 274-290, May 1985. Richardson, Rick, "Standards try to help-but don't always agree," Quality Magazine, USA, publication date unknown. S. Divakaruni et al., "Ring Laser Gyro Inertial and GPS Integrated Navigation System for Commercial Aviation," IEEE, pp. 73-80, 1986. Sakai, H., "Theoretical and Experimental Studies on the Dynamic Properties of Tyres Part I: Review of Rubber Friction," International Journal of Vehicle Design, pp. 78-110, 1981. Sakai, H., "Theoretical and Experimental Studies on the Dynamic Properties of Tyres, Part II: Experimental Investigation of Rubber Friction and Deformation of a Tyre," International Journal of Vehicle Design, pp. 182-226, 1981. Sakai, H., "Theoretical and Experimental Studies on the Dynamic Properties of Tyres, Part III: Calculation of the Six Components of Force and Moment of Tyre," International Journal of Vehicle Design, pp. 335-372, 1981. Savkoor, A. R., "The Lateral Flexibility of Pneumatic Tyre and Its Application to the Lateral Rolling Contact Problem," pp. 367-381, no date. Schwartz, H., "Sensitivity Analysis of an Integrated Navstar GPS/INS Navigation System to Component Failure," Journal of the Institute of Navigation, vol. 3, No. 4, pp. 325-337, 1983. Sennott, J. W., "Experimental Measurement and Characterization of Ionospheric Multipath Errors in Differential GPS", no date. Sennott, J., "Real-Time GPS and Loran-C Dynamical Performance for Critical Marine Applications," IEEE, pp. 1006-1009, 1981. Sennott, J. et al., "A Queuing Model for Analysis of A Bursty Multiple-Access Communication Channel," IEEE, pp. 317-321, 1981. Sheridan, T. "Three Models of Preview Control," IEEE Transactions on Human Factors in Electronics, pp. 91-102, June 1966. Sheth, P., et al., "A Generalized Symbolic Notation for Mechanism," Transactions of the ASME, pp. 102-112, February 1971. Sorenson, W., "Least-Squares estimation: From Gauss to Kalman," IEEE Spectrum, pp. 63-68, July 1970. T. Graettinger et al., "Evaluation and Time-Scaling of Trajectories for Wheeled Mobile Robots," ASME Journal of Dynamic Systems, Nov. 25, 1987. Taylor, Benjamin R., "CMM accuracy measurements," Quality Magazine, USA, 1986. Upadhyay, T., et al., "Benefits on Integrating GPS and Inertial Navigation," pp. 1-13, June 1982. Vaurus, J., "A Stimulation of an Imbedded Software System for Global Positioning System Navigation," Proceedings of the 1985 Winter Simulation Conference, pp. 586-590, 1985. Vehicle Dynamics Terminology, SAE J670e, 1984. VNIS '89 Conference Record, Sep. 11-13, 1989, Toronto, Canada, T. Saito et al. "Automobile Navigation System Using Beacon Information" pp. 139-145. W. Nelson, "Continuous Steering-Function Control of Robot Carts," AT&T Bell Laboratories, April 1988. W. Nelson, et al., "Local Path Control for an Autonomous Vehicle," AT&T Bell Laboratories, pp. 1504-1510, 1988. W. Uttal, "Teleoperators," Scientific American, pp. 124-129, December 1989. Wareby, Jan, "Intelligent Signaling: FAR & SS7", Cellular Business, pp. 58, 60 and 62, July 1990. Wescon/87 Conference Record, vol. 31, 1987, (Los Angeles, US) M. T. Allison et al "The next generation navigation system", pp. 941-947. Y. Goto et al., "The CMU System for Mobile Robot Navigation," The Robotics Institutes, Carnegie-Mellon University, pp. 99-105, 1987. Y. Kanayama et al., "A Locomotion Control Method for Autonomous Vehicles," pp. 1315-1317, 1988. Y. Kanayama et al., "Smooth Local Path-Planning for Autonomous Vehicles," Center for Robotic Systems and Microelectronics, University of California at Santa Barbara, Mar. 7, 1988. Yamada et al "GPS Navigator," Japanese Radio Technical Bulletin No. 24, 1986.

Brief Summary Text (53):

The position detector may also be linked to a mapping system and possibly a dead reckoning system, in order to pinpoint a position with a geographic landmark. Thus,

while precise absolute coordinate measurements of position may be used, it may also be possible to obtain useful data at reduced cost by applying certain presumptions to available data. In an automotive system, steering angle, compass direction, and wheel revolution information may be available, thereby giving a rough indication of position from a known starting point. When this information is applied to a mapping system, a relatively precise position may be estimated. Therefore, the required precision of another positioning system used in conjunction need not be high, in order to provide high reliability position information. For example, where it is desired to map potholes, positional accuracy of 10 cm may be desired, far more precise than might be available from a normal GPS receiver mounted in a moving automobile. However, when combined with other data, location and identification of such events is possible. Further, while the system may include or tolerate inaccuracies, it is generally desired that the system have high precision, as compensation for inaccuracies may be applied.

Brief Summary Text (59):

Potholes and other road obstructions and defects have two characteristics. First, they adversely effect vehicles which encounter them. Second, they often cause a secondary effect of motorists seeking to avoid a direct encounter or damage, by slowing or executing an evasive maneuver. These obstructions may therefore be detected in three ways; first, by analyzing the suspension of the vehicle for unusual shocks indicative of such vents; second, by analyzing speed and steering patterns of the subject vehicle and possibly surrounding vehicles; and third, by a visual, ultrasonic, or other direct sensor for detecting the pothole or other obstruction. Such direct sensors are known; however, their effectiveness is limited, and therefore an advance mapping of such potholes and other road obstructions greatly facilitates avoiding vehicle damage and executing unsafe or emergency evasive maneuvers. An advance mapping may also be useful in remediating such road hazards, as well.

Brief Summary Text (60):

Traffic jams occur for a variety of reasons. Typically, the road carries traffic above a threshold, and for some reason the normal traffic flow patterns are disrupted. Therefore, there is a dramatic slowdown in the average vehicle speed, and a reduced throughput. Because of the reduced throughput, even after the cause of the disruption has abated, the roadways may take minutes to hours to return to normal. Therefore, it is typically desired to have advance warnings of disruptions, which include accidents, icing, rain, sun glare, lane closures, road debris, police action, exits and entrances, and the like, in order to allow the driver to avoid the involved region or plan accordingly. Abnormal traffic patterns may be detected by comparing a vehicle speed to the speed limit or a historical average speed, by a visual evaluation of traffic conditions, or by broadcast road advisories. High traffic conditions are associated with braking of traffic, which in turn results in deceleration and the illumination of brake lights. Brake lights may be determined by both the specific level of illumination and the center brake light, which is not normally illuminated. Deceleration may be detected by an optical, radar or LIDAR sensor for detecting the speed and/or acceleration state of nearby vehicles.

Brief Summary Text (61):

While a preferred embodiment of the present invention employs one or more sensors, broadcast advisories, including those from systems according to or compatible with the present invention, provide a valuable source of information relating to road conditions and information of interest at a particular location. Therefore, the sensors need not form a part of the core system. Further, some or all of the required sensors may be integrated with the vehicle electronics ("vetronics"), and therefore the sensors may be provided separately or as options. It is therefore an aspect of an embodiment of the invention to integrate the transceiver, and event database into a vetronics system, preferably using a digital vetronics data bus to communicate with existing systems, such as speed sensors, antilock brake sensors, cruise control, automatic traction system, suspension, engine, transmission, and